

Connector Products April 2019

Edge Launch Key Features:

- No Soldering Required
- Top Ground Only
- Board Design Support Available
- Test Boards Available

Edge Launch Connectors

ELF110 1.0 mm (110 GHz) Edge Launch Connectors




Common Interface ELF110



Narrow Profile ELF110-001



Standard Profile ELF110-002



2" GCPW test board with typical data through 110 GHz



ELF67 1.85 mm (67 GHz) Edge Launch Connectors




Common Interface Narrow Profile ELF67



ELF67-001



Standard Profile ELF67-002



2" microstrip test board with typical data through 70 GHz



ELF50 2.40 mm (50 GHz) Edge Launch Connectors




Common Interface ELF50



Narrow Profile ELF50-001



Standard Profile ELF50-002



2" microstrip test board with typical data through 50 GHz



ELF40 2.92 mm (40 GHz) Edge Launch Connectors




Common Interface ELF40



Narrow Profile ELF40-001



Standard Profile ELF40-002



1" microstrip test board with typical data through 40 GHz



Elements of An Edge Launch Test Board Assembly






Field Replaceable Connectors FRF40 2.92 mm (40 GHz)

- 2.92 mm Interface
- Standard 2 & 4 Hole Flanges
- 40 GHz Bandwidth
- Rear Socket for 12 mil pin
- Low VSWR: DC-27.0 GHz.....1.10:1 27.0-40.0 GHz....1.15:1
- Temp Range -55° to +105°



FRF40-005



Typical test data through 40 GHz using FRF40-001 back-to-back connector pair with test pin.






Test Boards for Edge Launch Connectors (40 GHz)

- All test board launch designs are available at no charge in .pdf and .dxf formats
- 1" and 2" length microstrip and grounded coplanar waveguide (GCPW) boards available
- Available in both 40 GHz, 70 GHz and 110 GHz versions





40 GHz Test Board Part Numbers:

007-007-1Fn 1" Microstrip007-007-2Fn 2" Microstrip

008-008-1Fn 1" Grounded Coplanar Waveguide (GCPW)


008-008-2Fn 2" Grounded Coplanar

Waveguide (GCPW)

Typical test Data is shown in the Edge Launch Connector section. Demo boards are also available with sample connectors and test data.

Test Boards for Edge Launch Connectors (70 GHz)





70 GHz Test Board Part Numbers:

020-020-1Fn 1" Microstrip020-020-2Fn 2" Microstrip

021-021-1Fn 1" Grounded Coplanar Waveguide (GCPW)


021-021-2Fn 2" Grounded Coplanar

Waveguide (GCPW)

Test Boards for Edge Launch Connectors (110 GHz)



All test board designs are available to customers at no charge in .pdf and .dxf formats. Demo boards are also available with sample connectors and test data.



110 GHz Test Board Part Numbers:

044-044-1Fn 1" Microstrip044-044-2Fn 2" Microstrip

045-045-1Fn 1" Grounded Coplanar

Waveguide (GCPW)

045-045-2Fn 2" Grounded Coplanar

Waveguide (GCPW)

Top Launch Connectors

TLF40 2.92 mm (40 GHz)








TLF40-001


- Edge Launch Type Performance Anywhere on the Board
- 2.92 mm Connector for high speed digital industry with superior electrical performance
- · Compression fit, screw-on mounting, does not require soldering



1" microstrip test boa with typical data through 40 GHz

Test Boards for Top Launch Connectors

(40 GHz)














40 GHz Test Board Part Numbers:

086-086-1Fn 1" Microstrip

085-085-1.5Fn 1.5" Microstrip **088-088-1Fn** 1" Grounded Cop

1" Grounded Coplanar Waveguide (GCPW)

087-087-1.5Fn 1.5" Grounded Coplanar

Waveguide (GCPW)

Vertical Launch Connectors VLF40 2.92 mm (40 GHz)






hardware guidelines

available on our website

VLF40-002

 2.92 mm Connector for high speed digital industry with superior electrical performance

· Compression fit, screw-on mounting, does not require soldering




Typical data for 2 connectors tested as a back-to-back pair



Turnkey 0402 Package Test System


with 40 Ghz TRL/LRL Calibration and DUT Boards

This kit provides a total test fixture solution by providing both the TRL/LRL calibration board to calibrate the VNA to remove the connectors and 4 inches of the PCB trace from the measurement. Each test fixture contains 2.92 mm connectors on each end and a solder point for the SMD component for accurate measurements.



Plug & Play De-embedding Kit in Support of IEEE-P370

Our library of innovative designs led to this kit which includes 70 GHz test boards, 2.92 mm or 1.85 mm connectors, and a flush short, all using our own designed and manufactured boards and connectors. At DesignCon a paper, "A NIST Traceable PCB Kit..." will be presented by members of the committee which describes the use of this kit.




Complete P.C. Board Set (9 Boards Total) Frequency Range 040 (GHz) for 2.92 mm connectors 050 (GHz) for 2.40 mm connectors 070 (GHz) for 1.85 mm connectors


907

0X0


Broadband Test Verification Boards (40 GHz and 70 GHz)



DB40-002 Probe Verification Board




DB40-003 Basic Verification Board




907-040-10072 Anritsu Verification Board

"xxx" is a placeholder to define frequency range depending on connector types.

Calibration Boards (40 GHz and 70 GHz)




Part No. 907-xxx-10077




Part No. 907-xxx-10057

Cutaway Side View of a Mated Connector Pair




Connector Nomenclature



SMA/3.5mm/2.92mm

- SMA interface connectors (18/27 GHz bandwidth)
- 3.5mm interface connectors (33 GHz bandwidth)
- 2.92mm interface connectors (40 GHz bandwidth)
- All of these connectors are compatible with each other



2.40mm/1.85mm

- 2.40mm interface connectors (50 GHz bandwidth)
- 1.85mm interface connectors (70 GHz bandwidth)
- All of these connectors are compatible with each other





Image made using COMSOL Multiphysics® software and provided courtesy of COMSOL.

Signal Microwave, LLC

Chandler, Arizona info@signalmicrowave.com www.signalmicrowave.com (480) 322-4992 05032019

PCB Design Resources for Board Mount Connectors

- 3D models for simulation are available at no charge to help customers in their own development efforts.
- "Transparent Connections for 5G and WiGig Testing" that describes using 3D modeling tools to design board launches.



All Text and Images are Copyright © 2012–2019 Signal Microwave, LLC

